

## PRIMER MS

Cat. No. 327

Version 03/11

### Product Description

**Primer MS** is a polymeric solvent based material. It is applied cold.

### Application:

**Primer MS** is used as a prime coat over the following substrates prior to application of Multigum: concrete, bitumen membranes coated with aggregates, old acrylic coating, old asbestos roof, mineral or acrylic based coatings of external walls (prior to application of Multigum Matt).

**Primer MS** is also used on top of Flexigum in well sloped roofs, prior to application of Flexigum Top Coat.

### Consumption:

200 gr/sqm.

### Drying time:

1 – 2 hours, due to weather conditions.

### Package:

15 kg.

### Safety precautions:

- This product contains flammable solvents, only use it in well ventilated areas. Use personal protective gear.
- Avoid contact with hot surfaces, sparks, flames.
- Avoid breathing the material fumes.
- Avoid contact with skin, eyes.
- If swallowed do not induce vomiting and get prompt medical attention.
- Static discharge can cause fire.
- Empty containers retain product residues that can be dangerous and should be disposed properly.
- Wash your hands with water and soap after use.

The instructions that appear on the product are based on knowledge and experience amassed over the years. We reserve the right to change these instructions without prior notification. The operator is responsible for keeping informed of the latest updates. These instructions are solely recommendations and do not constitute liability for the product. Prior to use, the user must check the product's suitability, and the application and environmental conditions that meet his specifications. If in doubt, please contact us and we will be happy to instruct you.