

MASTICLEAR

Cat. no. 315

Version 08/16

Product Description

Masticlear is a clear, siloxane based liquid sealing of concrete surfaces, mineral surfaces or coated surfaces with washed aggregates.

Masticlear does not seal pores in concrete or cement, but coats with water absorption protective layer. Thus, the wall treated is water repellent, but “breathing” coating.

Purpose

Masticlear protects mineral or cement surfaces from water, soot, dirt etc. The material penetrates deep inside the treated base, dries fast without changing the surface appearance.

Instructions for use

1. Surface preparation – the surface shall be dry, clean of asphalt, oil, dust or any other substance. Concrete repairs or crack fillings, if any, shall be made before application of **Masticlear**.
2. After a rain the works shall be delayed for 2-3 days to allow the surface to dry.
3. Windows, shutters and doors shall be covered by polyethylene coating to prevent staining.
4. Use “Airless” or garden sprayer to apply **Masticlear**. On smooth walls a brush could be used. Proceed the treatment from the upper part of the wall downwards, in horizontal strips. Carry on with the treatment until saturation is reached and excessive material starts dripping. For the best results, two layers shall be applied length and breadth. The second layer shall be applied before the first layer dries. (wet on wet).

MASTICLEAR– white polymer waterproof material for roofs

Cat. no. 311

Version 08/16

Required Quantity

200-800 ml/m² for two layers according to the base absorbability.

Drying time

2-3 hours.

Packaging

17 lit., 5 lit.

Safety regulations:

- This product contains flammable solvents, only use it in well ventilated areas. Use personal protective gear.
- Avoid contact with hot surfaces, parks, flames.
- Avoid contact with skin, eyes.
- If swallowed do not induce vomiting and get prompt medical attention.
- Static discharge can cause fire.
- Empty containers retain product residues that can be dangerous and should be disposed properly.



FLAMMABLE

The instructions that appear on the product are based on knowledge and experience amassed over the years. We reserve the right to change these instructions without prior notification. The operator is responsible for keeping informed of the latest updates. These instructions are solely recommendations and do not constitute liability for the product. Prior to use, the user must check the product's suitability, and the application and environmental conditions that meet his specifications. If in doubt, please contact us and we will be happy to instruct you.